



R C VARIATIONS & SPECIFICATIONS

SIGNATURE

AVANTGARDE

ARRETÉ

IUC INDIVIDUAL UPGRADE	✓	✓	✓
LCC LOW COMPRESSION	✓	✓	✓
NESNO ENERGY STORAGE	✓	✓	✓
NCS NATURAL CRYSTAL STRUCTURE			✓
FGC FREEDOM GROUNDING® CONCEPT			✓
R AMT ARRETÉ			✓
R AMT		✓	
R EVOTECH SOFT DOME TWEETER	✓		
AUDIOVECTOR CARBON DRIVERS	✓	✓	✓
TITANIUM TECHNOLOGY COILS	✓	✓	✓
DFF CROSS-OVER TECHNOLOGY	✓	✓	✓
LAMINATED BAFFLES	✓	✓	✓
NON PARALLEL SURFACES	✓	✓	✓
NANOPORE DAMPING MATERIAL			✓
INTERNAL SHOCK ABSORBERS			✓
CARBON TERMINAL PLATE			✓
FREQUENCY RESPONSE	46-28 kHz	44-53 kHz	42-53 kHz
SENSITIVITY	91.5 dB	91.5 dB	91.5 dB
IMPEDANCE	8 Ohms	8 Ohms	8 Ohms
POWER HANDLING	275 W	300 W	350 W
X-OVER FREQUENCIES	3100 Hz	3000 Hz	2900 Hz
PRINCIPLE	2-way	2-way	2-way
BASS SYSTEM	Bass reflex	Bass reflex	Bass reflex
BASS/MID DRIVERS	6.5" Carbon	6.5" Carbon	6.5" Carbon
TREBLE DRIVER	R Evotech	R AMT	R AMT Arreté
DIMENSIONS CM (FOOTPRINT) HEIGHT/WIDTH/DEPTH	23,2 x 52,5 x 28,9	23,2 x 52,5 x 28,9	23,2 x 52,5 x 28,9