



ONWALL SPECIFICATIONS

SIGNATURE

AVANTGARDE

IUC INDIVIDUAL UPGRADE	✓	✓
LC LOW COMPRESSION	✓	✓
NE SNO ENERGY STORAGE	✓	✓
NCS NATURAL CRYSTAL STRUCTURE		
R AMT ARRETÉ		
R AMT		✓
R EVOTECH SOFT DOME	✓	
AUDIOVECTOR CARBON DRIVERS	✓	✓
DFF CROSS-OVER TECHNOLOGY	✓	✓
ALUMINIUM BAFFLES	✓	✓
NANOPORE DAMPING MATERIAL		
FREQUENCY RESPONSE	54-26 kHz	54-52 kHz
SENSITIVITY	88 dB	88 dB
IMPEDANCE	5 Ohms	5 Ohms
POWER HANDLING	150 W	180 W
X-OVER FREQUENCIES	800/3000 Hz	800/3000 Hz
PRINCIPLE	2-way	2-way
BASS SYSTEM	Bass reflex	Bass reflex
BASS/MID DRIVERS	5 "Carbon	5 "Carbon
TREBLE DRIVER	Evotech	AMT
DIMENSIONS CM (FOOTPRINT) HEIGHT/WIDTH/DEPTH	43 x 23 x 8,9	43 x 23 x 8,9



ARRETÉ



50-52 kHz

88 dB

5 Ohms

200 W

800/3000 Hz

2-way

Bass reflex

5" Carbon

AMT Arreté

43 x 23 x 8,9