



INWALL/INCEILING SPECIFICATIONS

SIGNATURE

AVANTGARDE

ARRETÉ

IUC INDIVIDUAL UPGRADE	✓	✓	✓
LC LOW COMPRESSION	✓	✓	✓
NES NO ENERGY STORAGE	✓	✓	✓
NCS NATURAL CRYSTAL STRUCTURE			✓
R AMT ARRETÉ			✓
R AMT		✓	
R EVOTECH SOFT DOME	✓		
AUDIOVECTOR CARBON DRIVERS	✓	✓	✓
DFF CROSS-OVER TECHNOLOGY	✓	✓	✓
ALUMINIUM BAFFLES	✓	✓	✓
NANOPORE DAMPING MATERIAL			✓
FREQUENCY RESPONSE	54-26 kHz	54-52 kHz	50-52 kHz
SENSITIVITY	88 dB	88 dB	88 dB
IMPEDANCE	5 Ohms	5 Ohms	5 Ohms
POWER HANDLING	150 W	180 W	200 W
X-OVER FREQUENCIES	800/3000 Hz	800/3000 Hz	800/3000 Hz
PRINCIPLE	2-way	2-way	2-way
BASS SYSTEM	Bass reflex	Bass reflex	Bass refl
BASS/MID DRIVERS	5 "Carbon	5 "Carbon	5 "Carbon
TREBLE DRIVER	AMT Arreté	AMT	Evotech
DIMENSIONS CM (FOOTPRINT) HEIGHT/WIDTH/DEPTH	43 x 23 x 8,9	43 x 23 x 8,9	43 x 23 x

