

Key Features	
Screen	49-inch diagonal Color Active Matrix TFT LED LCD - Full Sun
Resolution	up to 4k 3840 x 2160 @ 30hz
Aspect Ratio	16:9
Contrast Ratio	4000:1
Frame Rate	60Hz
Viewing Angle	178 °x 178 °
Response Time	8 milliseconds
TV formats	2160p, 1080p, 1080i, 720p, 720i, 480p, 480i
Input Connectors	
RF	Antenna/CATV (ATSC/QAM/NTSC) x1
HDBaseT Connections	up to 4k 3840 x 2160 @ 30hz
HDMI	HDMI Input x2 (HDMI 1.4, HDMI 2.0, HDCP 2.2) 3840 x 2160 @ 60hz
Control Set	IP Control, RS232 Serial, Discrete IR Control, Concealed rear IR Window
Audio Out	Digital Optical Toslink (Fixed) / Analog 1/8" headphone jack (Variable)
Speakers	Optional 20 WATT speaker bar (not Included) This model *does not include* built-in speakers.
Input Power	100-240 VAC, 50-60 Hz 2.0 A Max (288 Watts/2.4a@120v)
VIDEO COMPONENT	YPbPr plus Stereo Audio x1
RGB INPUT	VGA DB15hd (up to 1920x1080)
Operating Temperature	-24° to 122° F. (-31° to 50°C.)
Non-op. Temp	-24° to 140° F. (-31° to 60°C.)
VESA Mounting Pattern	400mm x 400mm
TV Dimensions	4.8 in. D x 26.9 in. H x 45.09 in. W
Shipping Dimensions	11 in. D x 35 in. H x 49.75 in. W
Accessories Included	Weatherproof Remote Control
Exterior	Powder-coated aluminum
TV Weight	84 lbs (38.1 kgs)
Shipping Weight	92 lbs (41.73 kgs)
Residential Warranty	Two year parts & labor
Commercial Warranty	Two year parts & labor

