



R 6 SPECIFICATIONS

SIGNATURE

AVANTGARDE

ARRETÉ

IUC INDIVIDUAL UPGRADE	✓	✓	✓
LC LOW COMPRESSION	✓	✓	✓
SEC SOUNDSTAGE ENHANCEMENT	✓	✓	✓
NES NO ENERGY STORAGE	✓	✓	✓
NCS NATURAL CRYSTAL STRUCTURE			✓
FGC FREEDOM GROUNDING® CONCEPT			✓
R AMT ARRETÉ			✓
R AMT		✓	
R EVOTECH SOFT DOME TWEETER	✓		
AUDIOVECTOR CARBON DRIVERS	✓	✓	✓
REAR FIRING MIDRANGE 3"			✓
ISOBARIC BASS REFLEX	✓	✓	✓
TITANIUM TECHNOLOGY COILS	✓	✓	✓
DFF CROSS-OVER TECHNOLOGY	✓	✓	✓
LAMINATED BAFFLES	✓	✓	✓
NON PARALLEL SURFACES	✓	✓	✓
NANOPORE DAMPING MATERIAL			✓
INTERNAL SHOCK ABSORBERS			✓
M8 PREMIUM SPIKES			✓
CARBON TERMINAL PLATE			✓
FREQUENCY RESPONSE	28 Hz – 26 kHz	26 Hz – 52 kHz	23 Hz – 52 kHz
SENSITIVITY	92,5 dB/W/m	91,5 dB/W/m	91,5 dB/W/m
IMPEDANCE	8 Ohms	8 Ohms	8 Ohms
POWER HANDLING	450 W	450 W	450 W
X-OVER FREQUENCIES	100/350/3000 Hz	100/350/3000 Hz	100/350/3000 Hz
PRINCIPLE	3.5-way	3.5-way	4.5-way
BASS SYSTEM	8 x 6,5" Isobaric Bass Reflex	8 x 6,5" Isobaric Bass Reflex	8 x 6,5" Isobaric Bass Reflex
BASS/MID DRIVERS	6.5" Carbon	6.5" Carbon	6.5" Carbon
REAR FIRING MIDRANGE DRIVER			3" Paper
TREBLE DRIVER	R Evotech	R AMT	R AMT Arreté
DIMENSIONS CM (FOOTPRINT) HEIGHT/WIDTH/DEPTH	123,4 x 27,8 x 43,1	123,4 x 27,8 x 43,1	123,4 x 27,8 x 43,1