

Technical specifications



	Confidence 60	Confidence 50	Confidence 30	Confidence 20
Sensitivity	87dB (2.83V / 1m)	87dB (2.83V / 1m)	88dB (2.83V / 1m)	87dB (2.83V / 1m)
IEC power handling	600W	400W	350W	250W
Impedance	4Ω (min 3.7 Ω @ 71Hz)	4Ω (min 2.7 Ω @ 79Hz)	4Ω (min 2.8 Ω @ 85Hz)	6Ω (min 5Ω @ 155Hz)
Frequency response (+/- 3dB)	29Hz-22kHz	35Hz-22kHz	38Hz-22kHz	42Hz-22kHz
Box principle	Bass-reflex down-firing port	Bass-reflex down-firing port	Bass-reflex down-firing port	Bass-reflex down-firing port
Crossover	3-way	3-way	3-way	2-way
Crossover frequency	200, 2580Hz	200, 2860Hz	290, 3700Hz	2325Hz
Crossover topology	2nd/3rd order with DDC	2nd/3rd order with DDC	2nd/3rd order with DDC	2nd order
Woofer	2x 23cm MSP	2x 18cm MSP	2x 18cm MSP	18cm MSP
Midrange	2x 15cm MSP	2x 15cm MSP	15cm MSP	-
Tweeter	28mm Esotar3	28mm Esotar3	28mm Esotar3	28mm Esotar3
Weight	66.2kg / 145.9lb	49.6 kg / 109.3lb	44.2 kg / 97.4lb	15.2 kg / 33.5lb
Weight including stand	-	-	-	27 kg / 59.6lb
Dimensions (W x H x D)	271 x 1634 x 469mm 10 ³ / ₈ x 64 x 18 ¹ / ₂ in	218 x 1512 x 399mm 8 ⁵ / ₈ x 59 ¹ / ₂ x 15 ³ / ₄ in	222 x 1337 x 399mm 8 ⁷ / ₈ x 52 ³ / ₈ x 15 ³ / ₄ in	223 x 520 x 414mm 8 ⁷ / ₈ x 20 ¹ / ₂ x 16 ¹ / ₄ in
Dimensions with feet/grille (W x H x D)	432 x 1679 x 517mm 17 x 66 ¹ / ₈ x 20 ³ / ₈ in	364 x 1557 x 424mm 14 ³ / ₈ x 61 ¹ / ₄ x 16 ³ / ₄ in	364 x 1382 x 424mm 14 ³ / ₈ x 54 ³ / ₈ x 16 ³ / ₄ in	223 x 520 x 444mm 8 ⁷ / ₈ x 20 ¹ / ₂ x 17 ¹ / ₂ in
Dimensions including stand (W x H x D)	-	-	-	368 x 1134 x 458mm 14 ¹ / ₂ x 44 ³ / ₈ x 18 in

Available finishes: Midnight High Gloss, Smoke High Gloss, Blonde Wood (on request: Raven Wood, Ruby Wood)

