



### R 3 SPECIFICATIONS

#### SIGNATURE

#### AVANTGARDE

#### ARRETÉ

IUC INDIVIDUAL UPGRADE	✓	✓	✓
LC LOW COMPRESSION	✓	✓	✓
SEC SOUNDSTAGE ENHANCEMENT	✓	✓	✓
NES NO ENERGY STORAGE	✓	✓	✓
NCS NATURAL CRYSTAL STRUCTURE			✓
FGC FREEDOM GROUNDING® CONCEPT			✓
R AMT ARRETÉ			✓
R AMT		✓	
R EVOTECH SOFT DOME TWEETER	✓		
AUDIOVECTOR CARBON DRIVERS	✓	✓	✓
TITANIUM TECHNOLOGY COILS	✓	✓	✓
DFF CROSS-OVER TECHNOLOGY	✓	✓	✓
LAMINATED BAFFLES	✓	✓	✓
NON PARALLEL SURFACES	✓	✓	✓
NANOPORE DAMPING MATERIAL			✓
INTERNAL SHOCK ABSORBERS			✓
CARBON TERMINAL PLATE			✓
FREQUENCY RESPONSE	26-28 kHz	23-53 kHz	23-53 kHz
SENSITIVITY	91 dB/W/m	90.5 dB/W/m	90.5 dB/W/m
IMPEDANCE	8 Ohms	8 Ohms	8 Ohms
POWER HANDLING	275 W	300 W	350 W
X-OVER FREQUENCIES	230/3100 Hz	280/3000 Hz	320/2900 Hz
BASS SYSTEM	Floor bass reflex	Floor bass reflex	Floor bass reflex
BASS/MID DRIVERS	6.5 " Carbon	6.5 " Carbon	6.5 " Carbon
TREBLE DRIVER	R Evotech	R AMT	R AMT Arreté
DIMENSIONS CM (FOOTPRINT) HEIGHT/WIDTH/DEPTH	103,4 x 23 x 36	103,4 x 23 x 36	103,4 x 23 x 36

